



BS-230 Clinical Chemistry Analyzer



Technical Specifications

System function Automatic, Discrete, Random Access, Bench-top STAT sample priority Throughput: Up to 200 tests/hour, up to 400 tests/hour with ISE Measuring principles: Absorbance photometry, Turbidimetry, Ion Selective Electrode technology Methodology: End-point, Fixed-time, Kinetic, optional ISE, Single/Dual/ reagent chemistries, monochromatic / bi-chromatic Original system pack reagent ready to use Close system and open system is optional Reagent/Sample Handling Reagent/Sample tray: 80 positions for reagents and 40 positions

for samples in 24-hour refrigerated compartment (2~12°C) Reagent volume: 100~250µl, step by 0.5µl Sample volume: 2~45µl, step by 0.1µl Reagent/Sample probe: Liquid level detection, vertical collision protection and inventory checking, reagent pre-warming Probe cleaning: Automatic washing for interior and exterior Carry over < 0.05% Automatic sample dilution: Pre-dilution and post-dilution

Internal bar code reader (optional) Capable to communicate with LIS in bi-directional mode

Reaction System: Cuvette: 40 disposable cuvettes Reaction volume: 100~360µl Operating temperature: 37 °C ±0.1 °C



Head office: FusionGreen Healthcare Pvt Ltd Krishna Ground Floor No. 51/6, First link street, Raghavan Colony, Ashok Nagar, Chennai-600 083, Tamil Nadu, India.

Branch Offices: Coimbatore & Madurai

ISE Module (optional) Measuring K+, Na+, Cl-

Mixing Unit Independent mixing bar

Optical System

Light Source:	Halogen-tungsten lamp
Wavelength:	8 wavelengths, 340nm、 405nm、 450nm、
	510nm、546nm、578nm、630nm、670nm
Absorption range:	0~4.0 Abs (10mm conversion), resolution
	0.0001Abs
Stray Light	5.6Abs

Control and Calibration

Calibration modes: Linear (one point, two points and		
	multi-points), Logit-Log 4P, Logit-Log 5P,	
	spline, exponential, polynomial, parabola	
Control Rules:	X-R, L-J, Westgard multi-rule, Cumulative sum	
	check, twin plot	

Operation Unit

Operation system: Windows 8 Interface: RS-232

Working Conditions

Power Supply:	200~240V, 50/60Hz, ≤1000VA or 100~130V,
	60Hz, ≤1000VA
Dimension:	690 mm (length) ×580 mm (depth) ×595 mm
	(height)
Weight:	47 kg
Water Consumption: $\leq 2 L/H$	

